

9 October 2024

Original: English

(24-7061) Page: 1/2

## **Committee on Technical Barriers to Trade**

## **NOTIFICATION**

The following notification is being circulated in accordance with Article 10.6

1. Notifying Member: EGYPT

If applicable, name of local government involved (Article 3.2 and 7.2):

2. Agency responsible:

Egyptian Organization for Standardization and Quality 16 Tadreeb El-Modarrebeen St., Ameriya, Cairo – Egypt

E-mail: <a href="mailto:eos@idsc.net.eg">eos@idsc.net.eg</a> / <a href="mailto:eos@idsc.net.eg">eos.tbt@eos.org.eg</a>

Website: <a href="http://www.eos.org.eq">http://www.eos.org.eq</a>

Tel.: + (202) 22845528 Fax: + (202) 22845504

Name and address (including telephone and fax numbers, email and website addresses, if available) of agency or authority designated to handle comments regarding the notification shall be indicated if different from above:

- 3. Notified under Article 2.9.2 [X], 2.10.1 [ ], 5.6.2 [ ], 5.7.1 [ ], 3.2 [ ], 7.2 [ ], other:
- 4. Products covered (HS or CCCN where applicable, otherwise national tariff heading. ICS numbers may be provided in addition, where applicable): Pumps (ICS code(s): 23.080)
- **5. Title, number of pages and language(s) of the notified document:** Draft of Egyptian standard for " Pumps. Rotodynamic pumps. Minimum required efficiency of water pumps and determination of Minimum Efficiency Index (MEI)";; (49 page(s), in English)
- **6. Description of content:** This draft of Egyptian standard specifies performance requirements (methods and procedures for testing and calculating) for determining the Minimum Efficiency Index (MEI) of rotodynamic glanded water pumps for pumping clean water, including where integrated in other products.

The pump types and sizes covered by this document are described in the Annex A. These pumps are designed and produced as duty pumps for pressures up to 16 bar for end suction pumps and up to 25 bar for multistage pumps, for all pumps designed for fluid temperatures between -10 °C and +120 °C. Also covered are 4" (10,16 cm) and 6" (15,24 cm) submersible multistage pumps designed for fluid temperatures between 0 °C and 90 °C

Worth mentioning is that this Draft standard adopts the technical content of BS EN 16480:2021

7. Objective and rationale, including the nature of urgent problems where applicable: Safety and quality requirements

8. Relevant documents:

BS EN 16480:2021

**9. Proposed date of adoption:** To be determined

Proposed date of entry into force: To be determined

**10. Final date for comments:** 60 days from notification

11. Texts available from: National enquiry point [X] or address, telephone and fax numbers and email and website addresses, if available, of other body:

Egyptian Organization for Standardization and Quality

Address: 16 Tadreeb El-Modarrebeen St., Ameriya, Cairo- Egypt

E-mail: <a href="mailto:eos@idsc.net.eg">eos@idsc.net.eg</a> / <a href="mailto:eos@idsc.net.eg">eos.tbt@eos.org.eg</a>

Website: http://www.eos.org.eq

Tel: + (202) 22845528 Fax: + (202) 22845504